

6.0 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 6.5 kVA, 230V, 3000RPM
- (Automatic Voltage Regulator)
- 12 Volt Electric Starter
- 16 Litre Fuel Tank
- Open Version (± 76 dBa)
- Single cylinder, air-cooled, 4-stroke, OHV
- Single Phase Output
- HJ-301 3in1 meter Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection



GENERAL DATA	
Model:	BP6500OP
Prime Power (P.R.P):	6.0 kVA
Stand-by Power (L.T.P):	6.5 kVA
Amps:	28 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	3000 RPM
Length:	720 mm
Width:	530 mm
Height:	610 mm
Weight:	75 kg's
Tank Capacity:	16 l

ADDITIONAL	
Running Time:	8 @ full load
Structure Type:	Open
Noise Level (7m):	76 dBA
Auto Voltage Regulator:	
ISO9001 Certified:	Yes
CE Certified:	Yes

ENGINE DATA	
Brand:	Bundu Power
Model:	LT420 - Air Cooled
Type:	Single cylinder, air-cooled, 4-stroke, OHV
Starting System:	12 Volt Electric Starter
Auto-Decompression:	Yes
Cubic Capacity (l):	0.420
Compression Ratio:	
Rated Power (kW/RPM):	6.5 / 3000
Fuel Type:	Petrol
Lube Oil:	10W-30 / SAE30
Low Pressure Alert:	No
Low Fuel Cut Out:	No

CONTROL PANEL	
Model:	HJ-301 3in1 meter
Type:	Digital Control Panel
Analogue Inputs:	N/A
Mains Phase Voltage:	No
Mains Line Voltage:	No

ALTERNATOR	
Model:	-
Pole Number:	2
Excitation Mode:	Self Excitation

* Specs subject to change without prior notice.

* Measurements based on ISO8528-1 Standards

* All rating at Sea Level, 25°C Ambient Temp.