

8.5 KVA PETROL GENERATOR

FEATURES & BENEFITS

- Maximum 9.5 kVA, 230V, 3000RPM
- Constant voltage AVR (Automatic Voltage Regulator)
- 12 Volt Electric Starter
- 25 Litre Fuel Tank
- Silent Version (± 66 dBa)
- 2-cylinders, air-cooled, 4-stroke, OHV
- Single Phase Output
- Datakom DKG-116 Digital Control Panel
- Low oil pressure system
- Low water cut out engine protection



GENERAL DATA	
Model:	BP9500SP
Prime Power (P.R.P):	8.5 kVA
Stand-by Power (L.T.P):	9.5 kVA
Amps:	41 A
Power Factor / COS:	1
Frequency:	50 Hz
Voltage:	230 V
Phases:	Single Phase
Engine Speed:	3000 RPM
Length:	990 mm
Width:	650 mm
Height:	945 mm
Weight:	218 kg's
Tank Capacity:	25 l

ADDITIONAL	
Running Time:	12 @ full load
Structure Type:	Silent
Noise Level (7m):	66 dBA
Auto Voltage Regulator:	Constant voltage AVR
ISO9001 Certified:	Yes
CE Certified:	Yes

ENGINE DATA	
Brand:	Bundu Power
Model:	LT620 - Air Cooled
Type:	2-cylinders, air-cooled, 4-stroke, OHV
Starting System:	12 Volt Electric Starter
Auto-Decompression:	Yes
Cubic Capacity (l):	0.62
Compression Ratio:	
Rated Power (kW/RPM):	
Fuel Type:	Petrol
Lube Oil:	10W-30 / SAE30
Low Pressure Alert:	Yes
Low Fuel Cut Out:	Yes

CONTROL PANEL	
Model:	Datakom DKG-116
Type:	Digital Control Panel
Analogue Inputs:	N/A
Mains Phase Voltage:	No
Mains Line Voltage:	No

ALTERNATOR	
Model:	-
Pole Number:	2
Excitation Mode:	Self Excitation

* Specs subject to change without prior notice.

* Measurements based on ISO8528-1 Standards

* All rating at Sea Level, 25°C Ambient Temp.