

1035.0 kVA PERKINS GENERATOR

FEATURES & BENEFITS

- Maximum 1138.0 kVA, 400 V, 1500 RPM
- Industrial brushless alternator with AVR
- Steel baseframe, retention basin & fuel tank with sensor
- Connect directly to a bulk tank (No integrated tank)
- Test report, manuals and electrical drawings supplied
- Modular design, open and silent version available
- Industrial silencer and coupling flange
- Electrical panel mounted on board the unit with digital control device installed in metal box
- Compact for easy handling and use
- World wide after sales service and technical support



GENERAL DATA	
Model:	P1050U
Continuous power (PRP):	1035.0 kVA
Continuous power (PRP):	828.0 kW
Stand-by power (LTP):	1138.0 kVA
Stand-by power (LTP):	910.4 kW
Power factor:	0.8
Frequency (Hz):	50 Hz
Voltage (V):	400 V
Width:	0 mm
Length:	0 mm
Height:	0 mm
Weight:	8410 kgs
Tank Capacity:	0 l
dBa @ 7m:	N/A

ALTERNATOR	
Alternator brand:	STAMFORD
Alternator model:	HCI6J
L.T.P. Power:	1155.0 kVA
P.R.P. Power:	1050.0 kVA
Connection:	Star
Phases:	Three phases with neutral
Terminal Number:	6
IP Protection:	23
Alternate Alternator:	STAMFORD / HCI6J

ENGINE DATA	
Brand:	PERKINS
Model:	4008TAG2A
Cylinders:	8
RPM:	1500
Cubic Capacity:	30.56
Air Intake:	Turbocharged
Standard Voltage:	24
SAE:	0-18
BMEP:	2320
Cooling:	Water
Flywheel P.R.P. Power:	872.0 kW
Flywheel Stand-by Power:	958.0 kW
Oil Qty:	165.6 l
Antifreeze Qty:	48.0 l
Heat from Radiator:	332.0 kW
Heat from Exhaust:	698.0 kW
Exhaust Temperature:	438 °C
Cooling Airflow:	0.00 m³/min
Combustion Airflow:	75.00 m³/min
Exhaust Airflow:	200.00 m³/min
TA Luft / TA Luft 2:	Not available / Not available
Stage:	Not available

FUEL CONSUMPTION	
Fuel Cons. at 110%:	248.0 l/h
Fuel Cons. at 100%:	220.0 l/h
Fuel Cons. at 75%:	160.0 l/h
Fuel Cons. at 50%:	108.0 l/h
Fuel Cons. at 25%:	57.0 l/h

* Specs subject to change without prior notice.
 * Measurements based on ISO8528-1 Standards
 * Picture may vary from actual product.